Shishu Stitch

Interface

Installation Method



Ashlar Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Shishu Stitch CQuest™BioX **Colour** Taupe **Collection** Embodied Beauty Collection **Backing**

Product Specifications	
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon contains recycled content
Standard Backing	CQuest™Bio X
Size	25cm x 1m
Tiles per Box	20 - 5m²
More Product Specifications	
Pile Yarn Weight	407 g/m² ± 5%
Total Weight	3,326 g/m² ± 5%
Pile Height	2.0 mm +15% / - 10%
Total Thickness	5.7 mm ±0.5mm
Gauge - Ends per 10 cm	1/12 - 47.2
Tufts per m²	330260 /m² ±5%
Performance Specifications	
Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	36.39
Light Reflectance Value (LRV-Y)	9.21
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	24 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.15
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.00
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.04
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.07
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.15
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.27
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.32
Environmental Specifications	
Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	CQuest™Bio X
Total Recycled Content	34 %
Pre-Consumer (Total)	32.90 %
Post-Consumer (Total)	1.10 %
Yarn Recycled Content	40.00 %
Pre-Consumer (Yarn)	31.00 %
Post-Consumer (Yarn)	9.00 %
Total Bio Based Content	48.7 %
Total Recycled & Bio Based Content	82.7 %
Indoor Air Quality	Compliant with LEED EQ 5.0 credit French A+ GLP 100209 M1 Emission Certification -CQB

HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	-0.3 kg CO_2 eq./m^2
Installation Waste	Herringbone 3-5% Ashlar – 3-5 %
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Certifications



24 dB

0.15

≥ 7

0.07

≥2.4