

Warranty	10 years*	Environment, health and safety
Composition	83% vinyl 7% fiberglass 10% PET	Recycled Content Yes
Backing	Vinyl + Felt	Acoustical layer 70% recycled content
Total thickness	ISO 1765 5 mm 0.20"	Reach Compliant
Total weight	ISO 8543 3000 g/m ² 88.5 oz/yd ²	LEED v4 Compliant (LEED Contributing Product)
Roll width	EN ISO 24341 ca. 200 cm ca. 6'7"	BREEAM International Compliant
Roll length	EN ISO 24341 ca. 30 m 32.8 yd	CDPH Standard Method V1.2 Pass
Tile size 16 pcs per box	EN 994 50 cm x 50 cm 19.69" x 19.69"	BREEAM® NOR Pass
Level of Use	EN 1307 ASTM D5252 Class 33 Heavy commercial use	French VOC Regulation A+ Certified
Foot traffic test	ASTM D6119-12 Heavy traffic	French CMR components Pass
Castor chair suitability	EN 985 Continuous use	AGBB/ABG Pass
Reaction to fire	EN 13501-1 ASTM E84 Bfl-s1 Class 1 - A rating	Belgian VOC Regulation Pass
Critical radiant flux	ASTM E648-15e1 NFPA 0,84 W/cm ² Class I	Indoor Air Comfort Gold Pass
Smoke density	ASTM E622 < 300	Blue Angel (RAL UZ120) Pass
Walking test	ISO 6356 AATCC 134-2006 < 2 kv Permanently antistatic	EN 717-1 E1
Light fastness	ISO 105-B02 ≥ 8	M1 Protocol of July 2017 Pass
Slip resistance	EN 13893 ASTM C1028-07 DIN 51130 EM 13036-4 ≥ 0,3 0,85 R9 65	Plasticizer Content Phthalate Free
Impact sound reduction	ISO 10140 19 dB	
Acoustical absorption	ISO 354 αw = 0,15	
Walking noise reduction	EPLF 021029-3 SL70	
Dimensional stability	EN 986 ISO 2551 Meets the requirements	
Thermal resistance	ISO 8302 Suitable for underfloor heating	
CE Certificate	EN 14041 0493-CPR-0151	

Co² neutral on demand - *Terms and conditions are available on request

0.2