


X. SB: BAS.0010



X. SB: BAS.0830



X. SB: BAS.0490




X. SB: BAS.0590



X. SB: BAS.0790



X. SB: BAS.0810



X. SB: BAS.0820



X. SB: BAS.0800



X. SB: BAS.0110



X. SB: BAS.0300



X. SB: BAS.0400




X. SB: BAS.0270



X. SB: BAS.0280



X. SB: BAS.0420



X. SB: BAS.0410



X. SB: BAS.0250



X. SB: BAS.0460



X. SB: BAS.0880



X. SB: BAS.0840



# Basalt Vintage



**X.**  
A touch of luxury.



# Basalt vintage

|  |                       |
|--|-----------------------|
| <b>Secondary Backing</b><br>Rugtype • Envers<br>Rücken • Sottofondo • Reverso  | <b>SB</b>             |
| <b>Manufacturing process</b><br>Fabricagemethode • Technique de fabrication<br>Herstellungstyp • Tecnica di fabbricazione • Técnica de fabricación                               | <b>1/10" CUT LOOP</b> |
| <b>Pile composition</b><br>Poolsamenstelling • Nature du velours<br>Polmaterial • Composizione felpa • Composición de pelo   | <b>PA</b>             |
| <b>Primary backing</b><br>Tuftdoek • Premier dossier<br>Trägermaterial • Tela di supporto • Tela de soporte  | <b>woven</b>          |
| <b>Width</b><br>Breedte • Largeur<br>Breite • Altezza • Ancho  | <b>± 400 cm</b>       |
| <b>Effective pile height</b><br>Nuttige poolhoogte • Hauteur de velours utile<br>Tatsächliche Florhöhe • Spessore felpa utile • Altura de pelo                                   | <b>± 5,5 mm</b>       |
| <b>Total height</b><br>Totale dikte • Hauteur totale<br>Gesamthöhe • Spessore totale • Altura total  | <b>± 7,5 mm</b>       |
| <b>Number of knots/sqm</b><br>Aantal noppen/m <sup>2</sup> • Nombre de points/m <sup>2</sup><br>Noppenzahl/m <sup>2</sup> • Numero di punti/mq • Puntos de pelo/m <sup>2</sup>   | <b>± 228.520</b>      |
| <b>Pile weight/sqm</b><br>Poolinzetgewicht/m <sup>2</sup> • Poids mis en oeuvre/m <sup>2</sup><br>Poleinsatzgewicht/m <sup>2</sup> • Peso felpa/mq • Peso de pelo/m <sup>2</sup> | <b>± 1.450 gr</b>     |
| <b>Total weight/sqm</b><br>Totaal gewicht/m <sup>2</sup> • Poids total/m <sup>2</sup><br>Gesamtwicht/m <sup>2</sup> • Peso totale/m <sup>2</sup> • Peso total/m <sup>2</sup>     | <b>± 2.495 gr</b>     |

|  |                          |
|--|--------------------------|
| <b>EN 13501-1 Fire behaviour</b><br>Brandgedrag • Comportement au feu<br>Brennverhalten • Reazione al fuoco • Resistencia al fuego | <b>B<sub>fl</sub>-s1</b> |
|--|--------------------------|

|  |  |
|--|--|
| <b>EN 1307-2004 Classification</b><br>Classificatie • Classification<br>Klassifizierung • Classificazione • Clasificación al uso | <b>Class 32</b><br><b>Commercial General</b> |
|--|--|

|  |                |
|--|----------------|
| <b>ISO 140/8 1997 Impact sound insulation</b><br>Contactgeluidsisolatie • Isolation aux bruits d'impact<br>Trittschallverbesserungsmaß • Miglioramento acustico • Aislamiento acústico | <b>± 25 dB</b> |
|--|----------------|

|   |                                 |
|---|---------------------------------|
| <b>DIN 52612 Thermal retention</b><br>Warmtedoorlaatweerstand • Résistivité thermique<br>Wärmedurchlaßwiderstand • Resistenza termica • Resistencia térmica | <b>± 0,075 m<sup>2</sup>/kW</b> |
|---|---------------------------------|

|                   |               |
|-------------------|---------------|
| <b>TOG Rating</b> | <b>± 0,75</b> |
|-------------------|---------------|

|  |            |
|--|------------|
| <b>ISO 105 B02 2000 Lightfastness</b><br>Lichtechtheid • Solidité à la lumière<br>Lichtechtheit • Solidità colori alla luce • Solidez del color a la luz | <b>≥ 5</b> |
|--|------------|

|   |              |
|---|--------------|
| <b>ISO 105 E01 2002 Waterfastness change in colour</b><br>Waterechtheid verkleuring • Solidité à l'eau changement couleur<br>Wasserechtheit Änderung der Farbe • Solidità colori all'acqua cambio colore<br>Solidez color al agua cambio de color | <b>≥ 3-4</b> |
|---|--------------|

|  |              |
|--|--------------|
| <b>ISO 105 E01 2002 Waterfastness staining</b><br>Waterechtheid uitbloeding • Solidité à l'eau dégorgement<br>Wasserechtheit anbluten • Solidità colori all'acqua sfumatura colore<br>Solidez color al agua pérdida de color | <b>≥ 2-3</b> |
|--|--------------|

|  |              |
|--|--------------|
| <b>ISO 105 X12 2001 Rubbingfastness dry</b><br>Wrijftechtheid droog • Solidité au frottement sec<br>Reibungstechtheit trocken • Solidità colori allo sfregamento a secco<br>Solidez del color a la frotación en seco | <b>≥ 3-4</b> |
|--|--------------|

|  |            |
|--|------------|
| <b>ISO 105 X12 2001 Rubbingfastness wet</b><br>Wrijftechtheid nat • Solidité au frottement humide<br>Reibungstechtheit nass • Solidità colori allo sfregamento umido<br>Solidez del color a la frotación en húmedo | <b>≥ 3</b> |
|--|------------|

(a) These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to improve technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet. For other languages see: [www.lano.com](http://www.lano.com)

The new EU chemicals legislation  
 21  
 EN 14041  
 DOP-1038-127932  
 NB 2401  
 B<sub>fl</sub>-s1  
 DS  
 LANO NV - Venetiëlaan 33  
 B-8530 HARELBEKE  
 Floor carpets to use in buildings  
 The Green signature of Lano Carpets  
 A9DC1EA1  
[www.gut-prodis.eu](http://www.gut-prodis.eu)



**Lano**  
Carpet Solutions

Venetiëlaan 33 • 8530 Harelbeke-Belgium  
t +32-56-65 40 00  
marketing@lano.be • www.lano.com