

# Jade



▲ SB: LJAD.0110 | 400 cm



▲ SB: LJAD.0780 | 400 cm



▲ SB: LJAD.0710 | 400 cm



▲ SB: LJAD.0850 | 400 cm



▲ SB: LJAD.0420 | 400 cm



▲ SB: LJAD.0800 | 400 cm



▲ SB: LJAD.0260 | 400 cm



▲ SB: LJAD.0820 | 400 cm



▲ SB: LJAD.0250 | 400 cm



▲ SB: LJAD.0840 | 400 cm



▲ SB: LJAD.0830 | 400 cm

# Jade

**Lano**  
Carpet Solutions

<b>Secondary Backing</b> Rugtype • Envers Rücken • Sottofondo	<b>SB</b>	<b>EN 13501-1 Fire behaviour</b> Brandgedrag • Comportement au feu Brennverhalten • Reazione al fuoco	<b>C<sub>fl-s1</sub></b>
<b>Manufacturing process</b> Fabricagemethode • Technique de fabrication Herstellungsart • Tecnica di fabbricazione	<b>1/10" cut pile</b>	<b>EN 1307-2004 Classification</b> Classificatie • Classification Klassifizierung • Classificazione	<b>Class 23 Domestic Heavy</b>
<b>Pile composition</b> Poolsamenstelling • Nature du velours Polmaterial • Composizione felpa	<b>PES</b>	<b>ISO 140/8 1997 Impact sound insulation</b> Contactgeluidsisolatie • Isolation aux bruits d'impact Trittschallverbesserungsmaß • Miglioramento acustico	<b>± 25 dB</b>
<b>Primary backing</b> Tuftdoek • Premier dossier Trägermaterial • Tela di supporto	<b>woven</b>	<b>DIN 52612 Thermal retention</b> Warmteoorlaatweerstand • Résistivité thermique Wärmedurchlaßwiderstand • Resistenza termica	<b>± 0,165 m<sup>2</sup>/kW</b>
<b>Width</b> Breedte • Largeur Breite • Altezza	<b>± 400 cm</b>	<b>TOG rating</b>	<b>± 1,65</b>
<b>Effective pile height</b> Nuttige poolhoogte • Hauteur de velours utile Tatsächliche Florhöhe • Spessore felpa utile	<b>± 10 mm</b>	<b>ISO 105 B02 2000 Lightfastness</b> Lichtechtheid • Solidité à la lumière Lichtechtheit • Solidità colori alla luce	<b>≥ 5</b>
<b>Total height</b> Totale dikte • Hauteur totale Gesamthöhe • Spessore totale	<b>± 12 mm</b>	<b>ISO 105 E01 2002 Waterfastness change in colour</b> Waterechtheid verkleuring • Solidité à l'eau changement couleur Wasserechtheit Änderung der Farbe • Solidità colori all'acqua cambio colore	<b>≥ 3-4</b>
<b>Number of knots/sqm</b> Aantal noppen/m <sup>2</sup> • Nombre de points/m <sup>2</sup> Noppenzahl/m <sup>2</sup> • Numero di punti/mq	<b>± 244.280</b>	<b>ISO 105 E01 2002 Waterfastness staining</b> Waterechtheid uitbloeding • Solidité à l'eau dégorgement Wasserechtheit anbluten • Solidità colori all'acqua sfumatura colore	<b>≥ 2-3</b>
<b>Pile weight/sqm</b> Poolinzetgewicht/m <sup>2</sup> • Poids mis en oeuvre/m <sup>2</sup> Poleinsatzgewicht/m <sup>2</sup> • Peso felpa/mq	<b>± 1.160 gr</b>	<b>ISO 105 X12 2001 Rubbingfastness dry</b> Wrijftechtheid droog • Solidité au frottement sec Reibungechtheit trocken • Solidità colori allo sfregamento a secco	<b>≥ 3-4</b>
<b>Total weight/sqm</b> Totaal gewicht/m <sup>2</sup> • Poids total/m <sup>2</sup> Gesamtwegicht/m <sup>2</sup> • Peso totale/m <sup>2</sup>	<b>± 2.230 gr</b>	<b>ISO 105 X12 2001 Rubbingfastness wet</b> Wrijftechtheid nat • Solidité au frottement humide Reibungechtheit nass • Solidità colori allo sfregamento umido	<b>≥ 3</b>

(±) These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to improve technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet. For other languages see: [www.lano.com](http://www.lano.com)

